

High Purity Wires

- Evaporation Wires
- Purity up to 99.999%



Material	Size (dia)	Purity	Melting Point
Aluminum (Al)	0.38mm (0.015")	99.99%	660.4°C
	0.5mm (0.02")	99.999%	
	1.0mm (0.04")	99.995%/99.999%	
	2.0mm (0.08")	99.995%/99.999%	
Cobalt (Co)	1.5mm (0.06")	99.95%	1495°C
	2.0mm (0.08")	99.95%	
	0.5mm (0.02")	99.995%	
Indium (In)	1.5mm (0.06")	99.99%	156.6°C
	2.0mm (0.08")	99.99%	
Iron (Fe)	0.5mm (0.02")	99.99%	1538°C
	1.0mm (0.08")	99.99%	
Nickel (Ni)	0.5mm (0.02")	99.98%	1455°C
	1.0mm (0.08")	99.98%	
Silver (Ag)	1.0mm (0.04")	99.999%	962°C
	1.5mm (0.06")	99.998%	
	2.0mm (0.08")	99.999%	
Tantalum (Ta)	0.5mm (0.02")	99.95%	2996°C
	1.0mm (0.08")	99.99%	
Tungsten (W)	0.25mm (0.01")	99.95%	3410°C
	1.0mm (0.04")	99.95%	
	1.25mm (0.049")	99.95%	
Zinc (Zn)	0.5mm (0.02")	99.95%	419.5°C
	1.0mm (0.04")	99.95%	
	2.0mm (0.08")	99.95%	
All available materials and sizes not listed.			



VIN KAROLA INSTRUMENTS

P.O. Box 922273
 Norcross, GA 30010-2273
 Tel: 770/409-1499
 Fax: 770/447-8045
 e-mail: info@vinkarola.com

Vin Karola reserves the right to make changes in Design, and specifications without notice or obligation.
 © Vin Karola Instruments, 2003-2009